





Hand pallet truck **AM 22 SH / 22 NH**

Lift height: 122 mm / Load capacity: 2200 kg

AM 22 SH / 22 NH



VDI table

Stand-on: 02/2024

Characteristic	1.1	Manufacturer (abbreviated description)		Jungheinrich
	1.2	Manufacturer's type designation		AM 22 NH
	1.3	Drive		Manual
	1.4	Operation		Manual
	1.5	Load capacity/load	Q	kg2200
	1.6	Load centre distance	c	mm300
	1.9	Wheelbase	y	mm560
Weights	2.1	tare weight		kg50
Wheels/suspension system	3.1	Tyres		C-BV
	3.2	Tyre size, front		Ø 170x50
	3.3	Tyre size, rear		Ø 82x96
	3.5	Wheels, number front/back (x=driven)		2/4
	3.6	Tread width, front	b10	mm109
	3.7	Tread width, rear	b11	mm370
Basic dimensions	4.4	Lift (h3)	h3	mm122
	4.9	Height of tiller handle in drive position min./max.	h14	mm359 / 1237
	4.14	Stand height, elevated	h12	mm205
	4.15	Height, lowered	h13	mm83
	4.19	total length	l1	mm973
	4.20	Length including fork shank	l2	mm373
	4.21.1	total width	b1	mm520
	4.22	Fork dimensions	s/e/l	mm53 x 150 x 600
	4.25	Width across forks	b5	mm520
	4.32	Ground clearance centre of wheelbase	m2	mm30
	4.34.1	Aisle width (pallet 1000x1200 sideways)	Ast	mm1584
	4.34.2	Aisle width (pallet 800x1200 length)	Ast	mm1784
	4.35	Turning radius	Wa	mm724
Performance data	5.3	Lowering speed laden/unladen		m/s0.09 / 0.02
- This data sheet according to VDI guideline 2198 only states the technical values of the standard truck. Different tyres, other masts, additional equipment etc. may result in different values.				

Characteristic	1.1	Manufacturer (abbreviated description)		Jungheinrich
	1.2	Manufacturer's type designation		AM 22 NH
	1.3	Drive		Manual
	1.4	Operation		Manual
	1.5	Load capacity/load	Q	kg2200
	1.6	Load centre distance	c	mm400
	1.9	Wheelbase	y	mm755

Weights	2.1	tare weight		kg	52
Wheels/suspension system	3.1	Tyres			C-BV
	3.2	Tyre size, front			Ø 170x50
	3.3	Tyre size, rear			Ø 82x96
	3.5	Wheels, number front/back (x=driven)			2/4
	3.6	Tread width, front	b10	mm	109
	3.7	Tread width, rear	b11	mm	370
Basic dimensions	4.4	Lift (h3)	h3	mm	122
	4.9	Height of tiller handle in drive position min./max.	h14	mm	359 / 1237
	4.14	Stand height, elevated	h12	mm	205
	4.15	Height, lowered	h13	mm	83
	4.19	total length	l1	mm	1168
	4.20	Length including fork shank	l2	mm	373
	4.21.1	total width	b1	mm	520
	4.22	Fork dimensions	s/e/l	mm	53 x 150 x 795
	4.25	Width across forks	b5	mm	520
	4.32	Ground clearance centre of wheelbase	m2	mm	30
	4.34.1	Aisle width (pallet 1000x1200 sideways)	Ast	mm	1584
	4.34.2	Aisle width (pallet 800x1200 length)	Ast	mm	1784
	4.35	Turning radius	Wa	mm	919
Performance data	5.3	Lowering speed laden/unladen		m/s	0.09 / 0.02
- This data sheet according to VDI guideline 2198 only states the technical values of the standard truck. Different tyres, other masts, additional equipment etc. may result in different values.					

Characteristic	1.1	Manufacturer (abbreviated description)			Jungheinrich
	1.2	Manufacturer's type designation			AM 22 NH
	1.3	Drive			Manual
	1.4	Operation			Manual
	1.5	Load capacity/load	Q	kg	2200
	1.6	Load centre distance	c	mm	500
	1.9	Wheelbase	y	mm	910
Weights	2.1	tare weight		kg	56
Wheels/suspension system	3.1	Tyres			C-BV
	3.2	Tyre size, front			Ø 170x50
	3.3	Tyre size, rear			Ø 82x96
	3.5	Wheels, number front/back (x=driven)			2/4
	3.6	Tread width, front	b10	mm	109
	3.7	Tread width, rear	b11	mm	370

Basic dimensions	4.4	Lift (h3)	h3	mm	122
	4.9	Height of tiller handle in drive position min./max.	h14	mm	359 / 1237
	4.14	Stand height, elevated	h12	mm	205
	4.15	Height, lowered	h13	mm	83
	4.19	total length	l1	mm	1323
	4.20	Length including fork shank	l2	mm	373
	4.21.1	total width	b1	mm	520
	4.22	Fork dimensions	s/e/l	mm	53 x 150 x 950
	4.25	Width across forks	b5	mm	520
	4.32	Ground clearance centre of wheelbase	m2	mm	30
	4.34.1	Aisle width (pallet 1000x1200 sideways)	Ast	mm	1584
	4.34.2	Aisle width (pallet 800x1200 length)	Ast	mm	1784
	4.35	Turning radius	Wa	mm	1074
Performance data	5.3	Lowering speed laden/unladen		m/s	0.09 / 0.02

- This data sheet according to VDI guideline 2198 only states the technical values of the standard truck. Different tyres, other masts, additional equipment etc. may result in different values.

Characteristic	1.1	Manufacturer (abbreviated description)			Jungheinrich
	1.2	Manufacturer's type designation			AM 22 NH
	1.3	Drive			Manual
	1.4	Operation			Manual
	1.5	Load capacity/load	Q	kg	2200
	1.6	Load centre distance	c	mm	600
	1.9	Wheelbase	y	mm	1110
Weights	2.1	tare weight		kg	60
Wheels/suspension system	3.1	Tyres			C-BV
	3.2	Tyre size, front			Ø 170x50
	3.3	Tyre size, rear			Ø 82x96
	3.5	Wheels, number front/back (x=driven)			2/4
	3.6	Tread width, front	b10	mm	109
	3.7	Tread width, rear	b11	mm	370
Basic dimensions	4.4	Lift (h3)	h3	mm	122
	4.9	Height of tiller handle in drive position min./max.	h14	mm	359 / 1237
	4.14	Stand height, elevated	h12	mm	205
	4.15	Height, lowered	h13	mm	83
	4.19	total length	l1	mm	1523
	4.20	Length including fork shank	l2	mm	373
	4.21.1	total width	b1	mm	520
	4.22	Fork dimensions	s/e/l	mm	53 x 150 x 1150
	4.25	Width across forks	b5	mm	520
	4.32	Ground clearance centre of wheelbase	m2	mm	30
	4.34.1	Aisle width (pallet 1000x1200 sideways)	Ast	mm	1734
	4.34.2	Aisle width (pallet 800x1200 length)	Ast	mm	1784

	4.35	Turning radius	Wa	mm	1274
Performance data	5.3	Lowering speed laden/unladen		m/s	0.09 / 0.02
- This data sheet according to VDI guideline 2198 only states the technical values of the standard truck. Different tyres, other masts, additional equipment etc. may result in different values.					

Characteristic	1.1	Manufacturer (abbreviated description)			Jungheinrich
	1.2	Manufacturer's type designation			AM 22 NH
	1.3	Drive			Manual
	1.4	Operation			Manual
	1.5	Load capacity/load	Q	kg	2200
	1.6	Load centre distance	c	mm	600
	1.9	Wheelbase	y	mm	1110
Weights	2.1	tare weight		kg	61
Wheels/suspension system	3.1	Tyres			C-BV
	3.2	Tyre size, front			Ø 170x50
	3.3	Tyre size, rear			Ø 82x96
	3.5	Wheels, number front/back (x=driven)			2/4
	3.6	Tread width, front	b10	mm	109
	3.7	Tread width, rear	b11	mm	370
Basic dimensions	4.4	Lift (h3)	h3	mm	122
	4.9	Height of tiller handle in drive position min./max.	h14	mm	359 / 1237
	4.14	Stand height, elevated	h12	mm	205
	4.15	Height, lowered	h13	mm	83
	4.19	total length	l1	mm	1523
	4.20	Length including fork shank	l2	mm	373
	4.21.1	total width	b1	mm	520
	4.22	Fork dimensions	s/e/l	mm	53 x 150 x 1207
	4.25	Width across forks	b5	mm	520
	4.32	Ground clearance centre of wheelbase	m2	mm	30
	4.34.1	Aisle width (pallet 1000x1200 sideways)	Ast	mm	1734
	4.34.2	Aisle width (pallet 800x1200 length)	Ast	mm	1784
	4.35	Turning radius	Wa	mm	1274
Performance data	5.3	Lowering speed laden/unladen		m/s	0.09 / 0.02
- This data sheet according to VDI guideline 2198 only states the technical values of the standard truck. Different tyres, other masts, additional equipment etc. may result in different values.					

Characteristic	1.1	Manufacturer (abbreviated description)		Jungheinrich
	1.2	Manufacturer's type designation		AM 22 NH
	1.3	Drive		Manual
	1.4	Operation		Manual
	1.5	Load capacity/load	Q kg	2200
	1.6	Load centre distance	c mm	700
	1.9	Wheelbase	y mm	1320
Weights	2.1	tare weight	kg	70
Wheels/suspension system	3.1	Tyres		C-BV
	3.2	Tyre size, front		Ø 170x50
	3.3	Tyre size, rear		Ø 82x96
	3.5	Wheels, number front/back (x=driven)		2/4
	3.6	Tread width, front	b10 mm	109
	3.7	Tread width, rear	b11 mm	370
Basic dimensions	4.4	Lift (h3)	h3 mm	122
	4.9	Height of tiller handle in drive position min./max.	h14 mm	359 / 1237
	4.14	Stand height, elevated	h12 mm	205
	4.15	Height, lowered	h13 mm	83
	4.19	total length	l1 mm	1733
	4.20	Length including fork shank	l2 mm	373
	4.21.1	total width	b1 mm	520
	4.22	Fork dimensions	s/e/l mm	53 x 150 x 1360
	4.25	Width across forks	b5 mm	520
	4.32	Ground clearance centre of wheelbase	m2 mm	30
	4.34.1	Aisle width (pallet 1000x1200 sideways)	Ast mm	1933
	4.34.2	Aisle width (pallet 800x1200 length)	Ast mm	1933
	4.35	Turning radius	Wa mm	1484
Performance data	5.3	Lowering speed laden/unladen	m/s	0.09 / 0.02
- This data sheet according to VDI guideline 2198 only states the technical values of the standard truck. Different tyres, other masts, additional equipment etc. may result in different values.				

Characteristic	1.1	Manufacturer (abbreviated description)		Jungheinrich
	1.2	Manufacturer's type designation		AM 22 NH
	1.3	Drive		Manual
	1.4	Operation		Manual
	1.5	Load capacity/load	Q kg	1500
	1.6	Load centre distance	c mm	800
	1.9	Wheelbase	y mm	1560
Weights	2.1	tare weight	kg	82
Wheels/suspension system	3.1	Tyres		C-BV

	3.2	Tyre size, front			Ø 170x50
	3.3	Tyre size, rear			Ø 82x96
	3.5	Wheels, number front/back (x=driven)			2/4
	3.6	Tread width, front	b10	mm	109
	3.7	Tread width, rear	b11	mm	370
Basic dimensions	4.4	Lift (h3)	h3	mm	122
	4.9	Height of tiller handle in drive position min./max.	h14	mm	359 / 1237
	4.14	Stand height, elevated	h12	mm	205
	4.15	Height, lowered	h13	mm	83
	4.19	total length	l1	mm	1973
	4.20	Length including fork shank	l2	mm	373
	4.21.1	total width	b1	mm	520
	4.22	Fork dimensions	s/e/l	mm	53 x 150 x 1600
	4.25	Width across forks	b5	mm	520
	4.32	Ground clearance centre of wheelbase	m2	mm	30
	4.34.1	Aisle width (pallet 1000x1200 sideways)	Ast	mm	2173
	4.34.2	Aisle width (pallet 800x1200 length)	Ast	mm	2173
	4.35	Turning radius	Wa	mm	1724
Performance data	5.3	Lowering speed laden/unladen		m/s	0.09 / 0.02
- This data sheet according to VDI guideline 2198 only states the technical values of the standard truck. Different tyres, other masts, additional equipment etc. may result in different values.					

Characteristic	1.1	Manufacturer (abbreviated description)			Jungheinrich
	1.2	Manufacturer's type designation			AM 22 NH
	1.3	Drive			Manual
	1.4	Operation			Manual
	1.5	Load capacity/load	Q	kg	1000
	1.6	Load centre distance	c	mm	900
	1.9	Wheelbase	y	mm	1860
Weights	2.1	tare weight		kg	82
Wheels/suspension system	3.1	Tyres			C-BV
	3.2	Tyre size, front			Ø 170x50
	3.3	Tyre size, rear			Ø 82x96
	3.5	Wheels, number front/back (x=driven)			2/4
	3.6	Tread width, front	b10	mm	109
	3.7	Tread width, rear	b11	mm	370
Basic dimensions	4.4	Lift (h3)	h3	mm	122
	4.9	Height of tiller handle in drive position min./max.	h14	mm	359 / 1237
	4.14	Stand height, elevated	h12	mm	205
	4.15	Height, lowered	h13	mm	83
	4.19	total length	l1	mm	2273
	4.20	Length including fork shank	l2	mm	373
	4.21.1	total width	b1	mm	520

	4.22	Fork dimensions	s/e/l	mm	53 x 150 x 1900
	4.25	Width across forks	b5	mm	520
	4.32	Ground clearance centre of wheelbase	m2	mm	30
	4.34.1	Aisle width (pallet 1000x1200 sideways)	Ast	mm	2473
	4.34.2	Aisle width (pallet 800x1200 length)	Ast	mm	2473
	4.35	Turning radius	Wa	mm	2024
Performance data	5.3	Lowering speed laden/unladen		m/s	0.09 / 0.02
- This data sheet according to VDI guideline 2198 only states the technical values of the standard truck. Different tyres, other masts, additional equipment etc. may result in different values.					

Characteristic	1.1	Manufacturer (abbreviated description)			Jungheinrich
	1.2	Manufacturer's type designation			AM 22 NH
	1.3	Drive			Manual
	1.4	Operation			Manual
	1.5	Load capacity/load	Q	kg	500
	1.6	Load centre distance	c	mm	1200
	1.9	Wheelbase	y	mm	2360
Weights	2.1	tare weight		kg	90
Wheels/suspension system	3.1	Tyres			C-BV
	3.2	Tyre size, front			Ø 170x50
	3.3	Tyre size, rear			Ø 82x96
	3.5	Wheels, number front/back (x=driven)			2/4
	3.6	Tread width, front	b10	mm	109
	3.7	Tread width, rear	b11	mm	370
Basic dimensions	4.4	Lift (h3)	h3	mm	122
	4.9	Height of tiller handle in drive position min./max.	h14	mm	359 / 1237
	4.14	Stand height, elevated	h12	mm	205
	4.15	Height, lowered	h13	mm	83
	4.19	total length	l1	mm	2773
	4.20	Length including fork shank	l2	mm	373
	4.21.1	total width	b1	mm	520
	4.22	Fork dimensions	s/e/l	mm	53 x 150 x 2400
	4.25	Width across forks	b5	mm	520
	4.32	Ground clearance centre of wheelbase	m2	mm	30
	4.34.1	Aisle width (pallet 1000x1200 sideways)	Ast	mm	2973
	4.34.2	Aisle width (pallet 800x1200 length)	Ast	mm	2973
	4.35	Turning radius	Wa	mm	2524
Performance data	5.3	Lowering speed laden/unladen		m/s	0.09 / 0.02
- This data sheet according to VDI guideline 2198 only states the technical values of the standard truck. Different tyres, other masts, additional equipment etc. may result in different values.					

Characteristic	1.1	Manufacturer (abbreviated description)		Jungheinrich
	1.2	Manufacturer's type designation		AM 22 NH
	1.3	Drive		Manual
	1.4	Operation		Manual
	1.5	Load capacity/load	Q kg	2200
	1.6	Load centre distance	c mm	500
	1.9	Wheelbase	y mm	910
Weights	2.1	tare weight	kg	59
Wheels/suspension system	3.1	Tyres		C-BV
	3.2	Tyre size, front		Ø 170x50
	3.3	Tyre size, rear		Ø 82x96
	3.5	Wheels, number front/back (x=driven)		2/4
	3.6	Tread width, front	b10 mm	109
	3.7	Tread width, rear	b11 mm	370
Basic dimensions	4.4	Lift (h3)	h3 mm	122
	4.9	Height of tiller handle in drive position min./max.	h14 mm	359 / 1237
	4.14	Stand height, elevated	h12 mm	205
	4.15	Height, lowered	h13 mm	83
	4.19	total length	l1 mm	1323
	4.20	Length including fork shank	l2 mm	373
	4.21.1	total width	b1 mm	680
	4.22	Fork dimensions	s/e/l mm	53 x 150 x 950
	4.25	Width across forks	b5 mm	680
	4.32	Ground clearance centre of wheelbase	m2 mm	30
	4.34.1	Aisle width (pallet 1000x1200 sideways)	Ast mm	1584
	4.34.2	Aisle width (pallet 800x1200 length)	Ast mm	1784
	4.35	Turning radius	Wa mm	1074
Performance data	5.3	Lowering speed laden/unladen	m/s	0.09 / 0.02
- This data sheet according to VDI guideline 2198 only states the technical values of the standard truck. Different tyres, other masts, additional equipment etc. may result in different values.				

Characteristic	1.1	Manufacturer (abbreviated description)		Jungheinrich
	1.2	Manufacturer's type designation		AM 22 NH
	1.3	Drive		Manual
	1.4	Operation		Manual
	1.5	Load capacity/load	Q kg	2200
	1.6	Load centre distance	c mm	600
	1.9	Wheelbase	y mm	1110
Weights	2.1	tare weight	kg	63
Wheels/suspension system	3.1	Tyres		C-BV

	3.2	Tyre size, front			Ø 170x50
	3.3	Tyre size, rear			Ø 82x96
	3.5	Wheels, number front/back (x=driven)			2/4
	3.6	Tread width, front	b10	mm	109
	3.7	Tread width, rear	b11	mm	370
Basic dimensions	4.4	Lift (h3)	h3	mm	122
	4.9	Height of tiller handle in drive position min./max.	h14	mm	359 / 1237
	4.14	Stand height, elevated	h12	mm	205
	4.15	Height, lowered	h13	mm	83
	4.19	total length	l1	mm	1523
	4.20	Length including fork shank	l2	mm	373
	4.21.1	total width	b1	mm	680
	4.22	Fork dimensions	s/e/l	mm	53 x 150 x 1150
	4.25	Width across forks	b5	mm	680
	4.32	Ground clearance centre of wheelbase	m2	mm	30
	4.34.1	Aisle width (pallet 1000x1200 sideways)	Ast	mm	1734
	4.34.2	Aisle width (pallet 800x1200 length)	Ast	mm	1784
	4.35	Turning radius	Wa	mm	1274
Performance data	5.3	Lowering speed laden/unladen		m/s	0.09 / 0.02
- This data sheet according to VDI guideline 2198 only states the technical values of the standard truck. Different tyres, other masts, additional equipment etc. may result in different values.					

Characteristic	1.1	Manufacturer (abbreviated description)			Jungheinrich
	1.2	Manufacturer's type designation			AM 22 SH
	1.3	Drive			Manual
	1.4	Operation			Manual
	1.5	Load capacity/load	Q	kg	2200
	1.6	Load centre distance	c	mm	400
	1.9	Wheelbase	y	mm	755
Weights	2.1	tare weight		kg	52
Wheels/suspension system	3.1	Tyres			C-BV
	3.2	Tyre size, front			Ø 170x50
	3.3	Tyre size, rear			Ø 82x96
	3.5	Wheels, number front/back (x=driven)			2/4
	3.6	Tread width, front	b10	mm	109
	3.7	Tread width, rear	b11	mm	370
Basic dimensions	4.4	Lift (h3)	h3	mm	122
	4.9	Height of tiller handle in drive position min./max.	h14	mm	359 / 1237
	4.14	Stand height, elevated	h12	mm	205
	4.15	Height, lowered	h13	mm	83
	4.19	total length	l1	mm	1168
	4.20	Length including fork shank	l2	mm	373
	4.21.1	total width	b1	mm	520

	4.22	Fork dimensions	s/e/l	mm	53 x 150 x 795
	4.25	Width across forks	b5	mm	520
	4.32	Ground clearance centre of wheelbase	m2	mm	30
	4.34.1	Aisle width (pallet 1000x1200 sideways)	Ast	mm	1584
	4.34.2	Aisle width (pallet 800x1200 length)	Ast	mm	1784
	4.35	Turning radius	Wa	mm	919
Performance data	5.3	Lowering speed laden/unladen		m/s	0.09 / 0.02
- This data sheet according to VDI guideline 2198 only states the technical values of the standard truck. Different tyres, other masts, additional equipment etc. may result in different values.					

Characteristic	1.1	Manufacturer (abbreviated description)			Jungheinrich
	1.2	Manufacturer's type designation			AM 22 SH
	1.3	Drive			Manual
	1.4	Operation			Manual
	1.5	Load capacity/load	Q	kg	2200
	1.6	Load centre distance	c	mm	500
	1.9	Wheelbase	y	mm	910
Weights	2.1	tare weight		kg	56
Wheels/suspension system	3.1	Tyres			C-BV
	3.2	Tyre size, front			Ø 170x50
	3.3	Tyre size, rear			Ø 82x96
	3.5	Wheels, number front/back (x=driven)			2/4
	3.6	Tread width, front	b10	mm	109
	3.7	Tread width, rear	b11	mm	370
Basic dimensions	4.4	Lift (h3)	h3	mm	122
	4.9	Height of tiller handle in drive position min./max.	h14	mm	359 / 1237
	4.14	Stand height, elevated	h12	mm	205
	4.15	Height, lowered	h13	mm	83
	4.19	total length	l1	mm	1323
	4.20	Length including fork shank	l2	mm	373
	4.21.1	total width	b1	mm	520
	4.22	Fork dimensions	s/e/l	mm	53 x 150 x 950
	4.25	Width across forks	b5	mm	520
	4.32	Ground clearance centre of wheelbase	m2	mm	30
	4.34.1	Aisle width (pallet 1000x1200 sideways)	Ast	mm	1584
	4.34.2	Aisle width (pallet 800x1200 length)	Ast	mm	1784
	4.35	Turning radius	Wa	mm	1074
Performance data	5.3	Lowering speed laden/unladen		m/s	0.09 / 0.02
- This data sheet according to VDI guideline 2198 only states the technical values of the standard truck. Different tyres, other masts, additional equipment etc. may result in different values.					

Characteristic	1.1	Manufacturer (abbreviated description)		Jungheinrich
	1.2	Manufacturer's type designation		AM 22 SH
	1.3	Drive		Manual
	1.4	Operation		Manual
	1.5	Load capacity/load	Q kg	2200
	1.6	Load centre distance	c mm	600
	1.9	Wheelbase	y mm	1110
Weights	2.1	tare weight	kg	60
Wheels/suspension system	3.1	Tyres		C-BV
	3.2	Tyre size, front		Ø 170x50
	3.3	Tyre size, rear		Ø 82x96
	3.5	Wheels, number front/back (x=driven)		2/4
	3.6	Tread width, front	b10 mm	109
	3.7	Tread width, rear	b11 mm	370
Basic dimensions	4.4	Lift (h3)	h3 mm	122
	4.9	Height of tiller handle in drive position min./max.	h14 mm	359 / 1237
	4.14	Stand height, elevated	h12 mm	205
	4.15	Height, lowered	h13 mm	83
	4.19	total length	l1 mm	1523
	4.20	Length including fork shank	l2 mm	373
	4.21.1	total width	b1 mm	520
	4.22	Fork dimensions	s/e/l mm	53 x 150 x 1150
	4.25	Width across forks	b5 mm	520
	4.32	Ground clearance centre of wheelbase	m2 mm	30
	4.34.1	Aisle width (pallet 1000x1200 sideways)	Ast mm	1734
	4.34.2	Aisle width (pallet 800x1200 length)	Ast mm	1784
	4.35	Turning radius	Wa mm	1274
Performance data	5.3	Lowering speed laden/unladen	m/s	0.09 / 0.02
- This data sheet according to VDI guideline 2198 only states the technical values of the standard truck. Different tyres, other masts, additional equipment etc. may result in different values.				

Characteristic	1.1	Manufacturer (abbreviated description)		Jungheinrich
	1.2	Manufacturer's type designation		AM 22 SH
	1.3	Drive		Manual
	1.4	Operation		Manual
	1.5	Load capacity/load	Q kg	1500
	1.6	Load centre distance	c mm	800
	1.9	Wheelbase	y mm	1560
Weights	2.1	tare weight	kg	82
Wheels/suspension system	3.1	Tyres		C-BV

	3.2	Tyre size, front			Ø 170x50
	3.3	Tyre size, rear			Ø 82x96
	3.5	Wheels, number front/back (x=driven)			2/4
	3.6	Tread width, front	b10	mm	109
	3.7	Tread width, rear	b11	mm	370
Basic dimensions	4.4	Lift (h3)	h3	mm	122
	4.9	Height of tiller handle in drive position min./max.	h14	mm	359 / 1237
	4.14	Stand height, elevated	h12	mm	205
	4.15	Height, lowered	h13	mm	83
	4.19	total length	l1	mm	1973
	4.20	Length including fork shank	l2	mm	373
	4.21.1	total width	b1	mm	520
	4.22	Fork dimensions	s/e/l	mm	53 x 150 x 1600
	4.25	Width across forks	b5	mm	520
	4.32	Ground clearance centre of wheelbase	m2	mm	30
	4.34.1	Aisle width (pallet 1000x1200 sideways)	Ast	mm	2173
	4.34.2	Aisle width (pallet 800x1200 length)	Ast	mm	2173
	4.35	Turning radius	Wa	mm	1724
Performance data	5.3	Lowering speed laden/unladen		m/s	0.09 / 0.02
- This data sheet according to VDI guideline 2198 only states the technical values of the standard truck. Different tyres, other masts, additional equipment etc. may result in different values.					

Characteristic	1.1	Manufacturer (abbreviated description)			Jungheinrich
	1.2	Manufacturer's type designation			AM 22 SH
	1.3	Drive			Manual
	1.4	Operation			Manual
	1.5	Load capacity/load	Q	kg	1000
	1.6	Load centre distance	c	mm	900
	1.9	Wheelbase	y	mm	1860
Weights	2.1	tare weight		kg	82
Wheels/suspension system	3.1	Tyres			C-BV
	3.2	Tyre size, front			Ø 170x50
	3.3	Tyre size, rear			Ø 82x96
	3.5	Wheels, number front/back (x=driven)			2/4
	3.6	Tread width, front	b10	mm	109
	3.7	Tread width, rear	b11	mm	370
Basic dimensions	4.4	Lift (h3)	h3	mm	122
	4.9	Height of tiller handle in drive position min./max.	h14	mm	359 / 1237
	4.14	Stand height, elevated	h12	mm	205
	4.15	Height, lowered	h13	mm	83
	4.19	total length	l1	mm	2273
	4.20	Length including fork shank	l2	mm	373
	4.21.1	total width	b1	mm	520

	4.22	Fork dimensions	s/e/l	mm	53 x 150 x 1900
	4.25	Width across forks	b5	mm	520
	4.32	Ground clearance centre of wheelbase	m2	mm	30
	4.34.1	Aisle width (pallet 1000x1200 sideways)	Ast	mm	2473
	4.34.2	Aisle width (pallet 800x1200 length)	Ast	mm	2473
	4.35	Turning radius	Wa	mm	2024
Performance data	5.3	Lowering speed laden/unladen		m/s	0.09 / 0.02
- This data sheet according to VDI guideline 2198 only states the technical values of the standard truck. Different tyres, other masts, additional equipment etc. may result in different values.					

Characteristic	1.1	Manufacturer (abbreviated description)			Jungheinrich
	1.2	Manufacturer's type designation			AM 22 SH
	1.3	Drive			Manual
	1.4	Operation			Manual
	1.5	Load capacity/load	Q	kg	500
	1.6	Load centre distance	c	mm	1200
	1.9	Wheelbase	y	mm	2360
Weights	2.1	tare weight		kg	90
Wheels/suspension system	3.1	Tyres			C-BV
	3.2	Tyre size, front			Ø 170x50
	3.3	Tyre size, rear			Ø 82x96
	3.5	Wheels, number front/back (x=driven)			2/4
	3.6	Tread width, front	b10	mm	109
	3.7	Tread width, rear	b11	mm	370
Basic dimensions	4.4	Lift (h3)	h3	mm	122
	4.9	Height of tiller handle in drive position min./max.	h14	mm	359 / 1237
	4.14	Stand height, elevated	h12	mm	205
	4.15	Height, lowered	h13	mm	83
	4.19	total length	l1	mm	2773
	4.20	Length including fork shank	l2	mm	373
	4.21.1	total width	b1	mm	520
	4.22	Fork dimensions	s/e/l	mm	53 x 150 x 2400
	4.25	Width across forks	b5	mm	520
	4.32	Ground clearance centre of wheelbase	m2	mm	30
	4.34.1	Aisle width (pallet 1000x1200 sideways)	Ast	mm	2973
	4.34.2	Aisle width (pallet 800x1200 length)	Ast	mm	2973
	4.35	Turning radius	Wa	mm	2524
Performance data	5.3	Lowering speed laden/unladen		m/s	0.09 / 0.02
- This data sheet according to VDI guideline 2198 only states the technical values of the standard truck. Different tyres, other masts, additional equipment etc. may result in different values.					

Characteristic	1.1	Manufacturer (abbreviated description)			Jungheinrich
	1.2	Manufacturer's type designation			AM 22 SH
	1.3	Drive			Manual
	1.4	Operation			Manual
	1.5	Load capacity/load	Q	kg	2200
	1.6	Load centre distance	c	mm	500
	1.9	Wheelbase	y	mm	910
Weights	2.1	tare weight		kg	59
Wheels/suspension system	3.1	Tyres			C-BV
	3.2	Tyre size, front			Ø 170x50
	3.3	Tyre size, rear			Ø 82x96
	3.5	Wheels, number front/back (x=driven)			2/4
	3.6	Tread width, front	b10	mm	109
	3.7	Tread width, rear	b11	mm	370
Basic dimensions	4.4	Lift (h3)	h3	mm	122
	4.9	Height of tiller handle in drive position min./max.	h14	mm	359 / 1237
	4.14	Stand height, elevated	h12	mm	205
	4.15	Height, lowered	h13	mm	83
	4.19	total length	l1	mm	1323
	4.20	Length including fork shank	l2	mm	373
	4.21.1	total width	b1	mm	680
	4.22	Fork dimensions	s/e/l	mm	53 x 150 x 950
	4.25	Width across forks	b5	mm	680
	4.32	Ground clearance centre of wheelbase	m2	mm	30
	4.34.1	Aisle width (pallet 1000x1200 sideways)	Ast	mm	1584
	4.34.2	Aisle width (pallet 800x1200 length)	Ast	mm	1784
	4.35	Turning radius	Wa	mm	1074
Performance data	5.3	Lowering speed laden/unladen		m/s	0.09 / 0.02

- This data sheet according to VDI guideline 2198 only states the technical values of the standard truck. Different tyres, other masts, additional equipment etc. may result in different values.

Note. The tables do not represent all tyre variants. Not all tyre variants are available for all fork lengths.
Available tyres:
Steering wheels: N = nylon, C = rubber, V = polyurethane.
Load rollers: GN = single nylon, GV = single polyurethane, BN = tandem nylon, BV = tandem polyurethane.

The German production facilities in
Norderstedt, Moosburg and Landsberg
are certified as well as our Genuine Parts
Center in Kaltenkirchen. ISO 9001
ISO 14001

Jungheinrich fork lift trucks meet
European safety requirements.



 **JUNGHEINRICH**